PVC STRIP CURTAIN ORDER & FITTING GUIDE


PVC STRIP CURTAINS

- Used for internal and external thermal partitions, as a barrier against fumes, dust or flying insects, birds etc
- It may also be used to reduce noise levels between production areas and quiet areas
- Made from a high quality, low toxic, silicone free, cadmium free PVC material offering extremely good clarity and consistency of colour and dimensional tolerances
- Will resist the continual passage of vehicular traffic
- A "Buffer" quality is available for extreme conditions where "standard" material has a limited life

ORDERING & FITTING PVC STRIP CURTAIN KITS

1. SELECT FIXING METHOD

The hanging rail for the PVC curtains can be mounted in two configurations depending on the space available around the door frame / type of door frame





Face Fixing Mounted to the wall above the doorway

2. SELECT MATERIAL & SIZE

Use the table below to select the width, thickness & overlap for your traffic. Then use the left hand page to select material. For external doors subject to strong wind 400mm x 4mm and MAX overlap

Location	Traffic	Width & Thickness	Overlap
Internal Doors &	Pedestrian	200 x 2mm	MIN or MAX
Screens	Forklifts	300 x 2mm 300 x 3mm	MED or MAX
External Doors and Cold Stores	All	300 x 3mm	MED or MAX
	All	400 x 4mm	MED or MAX

3. MEASURE UP

For Soffit Fixing, measure the door frame width and door frame height

For Face Fixing, please measure the exact width of the door opening. And add the following extra dimensions, to ensure insulation at the sides:

- For 200mm, add 80mm per side
- For 300mm, add 90mm per side
- For 400mm, add 100mm per side

Please measure the exact height of the door and add a further 30mm to this dimension. This provides additional length to allow the hanging bars to be fitted above the door

When ordering, please specify if a marker strip is required at each side of the door

4. ORDERING

To help you collect and calculate the right dimentions to place an order, here's an example of a typical order for PVC strip curtains:

Example Order				
Fixing	Face Fixing			
Overlap	Medium			
Strip Curtain	300mm x 3mm			
Door Width	2.7m (+90mm to each side = 2.88m)			
Door Height	1.9m (+30mm for hanger = 1.93m)			
Total m²	2.88m x 1.93m = 5.58m ²			

5. FITTING PVC CURTAINS

- Your kit should include hanging rails and PVC curtain strips with hangers attached
- Hanging rails fit to either the soffit of the door frame or the wall with 3 subtle screws
- Hanging the PVC strips on the rail acording to the overlap that's been specified (E.g. MIN, MED or MAX - see illustration & tables below)

200mm Wide Strip Overlap					
MINI	Α	1 hook overlap of first and second layer of strips			
MIN	В	3 hook space in between each strip			
MAY	Α	2 hook overlap of first and second layer of strips			
MAX	В	1 hook space in between each strip			

300m	300mm Wide Strip Overlap						
MIN	Α	1 hook overlap of first and second layer of strips					
IVIIIN	В	5 hook space in between each strip					
MED	Α	2 hook overlap of first and second layer of strips					
INIED	В	3 hook space in between each strip					
MAX	Α	3 hook overlap of first and second layer of strips					
IVIAX	В	1 hook space in between each strip					

	В
400	mm Wide Strip Overlap

400mi	400mm Wide Strip Overlap							
MIN	Α	1 hook overlap of first and second layer of strips						
В		7 hook spaces in between each strip						
MED	Α	3 hook overlap of first and second layer of strips						
MED	В	3 hook space in between each strip						
MAX	Α	2 hook overlap of first and second layer of strips						
IVIAX	В	1 hook space in between each strip						

PVC STRIP CURTAIN ORDER & FITTING GUIDE

CLEAR PVC STRIP CURTAINS

High consistency of colour tint

- Made in a high quality, low toxic, Cadmium free PVC material
- Offers extremely good clarity
- · Great dimensional tolerances.

Working temperature: -15°C to +50°C

34.00



Clear Curtain Options		•	Complete Door Kits - Made to measure		Replacement Strips - Hanger & cut inc.			Full Rolls - 50m length	
Width	Thick- ness	Code (+ Overlap)	Price (per m²)	Co	ode	Price (per m)		Code	Price (per roll)
200mm	2mm	3402131 (MAX)	£36.00	34	02120	£4.50)	3402110	£102.00
300mm	2mm	3402133 (MED)	£34.00	34	02122	£7.00)	3402111	£170.00
200	2	3402134 (MED)	£43.00	24	00400	00.00		2402442	0040.00
300mm	3mm	3402137 (MAX)	£51.00	3402123		£8.00	'	3402113	£212.00
400mm	4mm	3402139 (MAX)	£61.00	34	02125	£15.00)	3402117	£403.00

POLAR PVC STRIP CURTAINS

- For low temperature applications
- Suitable for walk-in freezers and refrigerated vehicles
- Working temperature: -40oC to +50oC





Polar Cu Options	rtain	Complete Dod - Made to mea	•		Full Rolls - 50m length				
Width	Thick- ness	Code (+ Overlap)	Price (per m²)		Code	Price (per m)		Code	Price (per roll)
200mm	2mm	3402132 (MAX)	£38.00		3402126	£4.50		3402126R	£115.00
300mm	3mm	3402135 (MED)	£45.00		3402127	£9.00		3402115	£235.00
400mm	4mm	3402141 (MAX)	£71.00		3402128	£16.00		3402118	£458.00

BUFFER PVC STRIP CURTAINS

- For the most demanding impact conditions
- "Double Buffer" option will increase the life of the screen further
- Working temperature: -15oC to +50oC

£	from 45.00



Buffer C Options	urtain	Complete Dod - Made to mea		Replacement Strips - Hanger & cut inc.		Full Rolls - 50m length		
Width	Thick- ness	Code (+ Overlap)	Price (per m²)	Code	Price (per m)		Code	Price (per roll)
300mm	3mm	3402136 (MED)	£45.00	3402129	£9.00		3402116	£236.00
400mm	4mm	3402140 (MAX)	£64.00	3402130	£15.00		3402119	£436.00

WELDING CURTAINS

- Specialist version developed for use as welding curtains
- Meets specification EN1598
- Working temperature: -15oC to +50oC

Welding Curtain - 50 metre roll					
Width Thickness Code Price					
300mm	2mm	3402112	£170.00		

MARKER CURTAINS

- Used to highlight door frames
- Increases safety awareness



Red Marker Curtain							
Width	Thickness	Length	Code	Price			
300mm	3mm	50 Metre Roll	3402114	£212.00			
200mm	2mm	Linear Metre	3402121	£6.00			
300mm	3mm	Linear Metre	3402124	£8.00			







