

GALVANISED MIDISPAN RACKING – 8800KG CAPACITY



E3 Shelving Bay Size 2000 x 1000 x 400mm with Extension Bay

GY
RAL 7037

Hard Wearing Galvanised Steel Shelving, designed to optimise storage space with frame capacities up to 8800kg. Ideal for tough and demanding environments.

GENERAL INFO & FEATURES

- Frames and beam levels sold as separate components
- To build a 3 level bay like the image you will need to purchase 2x end frames and 3x beam levels
- Heavy-duty shelves which can hold capacities up to 750kg UDL
- Maximum bay load 8800kg
- **4 heights** available with **6 widths** and **4 depths**
- Beams are adjustable every 25mm
- Multi-tier or rack supported floors for additional capacity

APPLICATIONS

- Suiting a wide range of industries such as warehouses, workshops, automotive, storerooms, merchandising or supermarkets

ADDITIONAL INFO

- 5 Year Guarantee
- Various shelf options available with a wide choice of sizes



C50 Beams



C70 Beams



Midspan Feet (Can be Bolted)



Midspan Feet Close Up



Midspan Racking Client Installation Image

DIMENSIONS

| Frame Capacity | Shelf Capacity | Heights | Widths | Depths |
|----------------|--|--------------------------|--------------------------------------|------------------------|
| 8800kg | C50: up to 400kg UDL C70: up to 750kg UDL | 2550, 4500, 5550, 6000mm | 1000, 1200, 1600, 1800, 2000, 2400mm | 600, 800, 1000, 1200mm |

**WORKPLACE
PRODUCTS**

t. 01922 743 833 | e. sales@workplace-products.co.uk | w. workplace-products.co.uk

Workplace Products, Timmis Road, Lye, Stourbridge, West Midlands DY9 7BQ, United Kingdom

GALVANISED MIDISPAN RACKING - 8800KG CAPACITY

C50 PROFILE BEAM LEVEL CAPACITIES

| Width (mm) | Depth - 400mm | Depth - 600mm | Depth - 800mm | Depth - 1000mm | Depth - 1200mm |
|------------|---------------|---------------|---------------|----------------|----------------|
| 1000 | 400kg UDL | 400kg UDL | 400kg UDL | 350kg UDL | 325kg UDL |
| 1200 | 340kg UDL | 340kg UDL | 340kg UDL | 340kg UDL | 340kg UDL |
| 1600 | 250kg UDL | 250kg UDL | 250kg UDL | 250kg UDL | 250kg UDL |

C70 PROFILE BEAM LEVEL CAPACITIES

| Width (mm) | Depth - 400mm | Depth - 600mm | Depth - 800mm | Depth - 1000mm | Depth - 1200mm |
|------------|---------------|---------------|---------------|----------------|----------------|
| 1000 | 500kg UDL | 500kg UDL | 400kg UDL | 350kg UDL | 325kg UDL |
| 1200 | 600kg UDL | 600kg UDL | 480kg UDL | 420kg UDL | 390kg UDL |
| 1600 | 750kg UDL | 750kg UDL | 640kg UDL | 560kg UDL | 520kg UDL |
| 1800 | 660kg UDL | 660kg UDL | 660kg UDL | 630kg UDL | 585kg UDL |
| 2000 | 600kg UDL | 600kg UDL | 600kg UDL | 600kg UDL | 600kg UDL |
| 2400 | 480kg UDL | 480kg UDL | 480kg UDL | 480kg UDL | 480kg UDL |

